



## METEOROLOGICAL EQUIPMENT

### ED-WIND DIRECTION SENSOR COS/SIN 4 KHz

#### FEATURES

- Very high accuracy
- 0 - 360° measurement
- Better than 0.1° resolution
- High wind speeds >60m/s
- 5-pole plug connection
- Removable vane

#### APPLICATIONS

- Research and scientific measurements
- Wind farms
- Environmental monitoring and warning
- Agriculture - Industry - Aviation
- Meteorological Stations



#### TECHNICAL CHARACTERISTICS

The ED-Wind Direction Sensor cos/sin 4KHz is a counter-balanced and low-threshold wind vane with a cos/sin output voltage, proportional to the angle of the vane. The signal transducer is a brushless resolver with an effective angle of 360°, a resolution better than 0.1°, and an electric error better than +/- 10 minutes.

This type of wind direction sensor is used worldwide at wind farms, airports and meteorological stations.

The body is made of painted brass, and the vane of anodized aluminium, very suitable for environment with salinity, high wind speeds and wide temperature range.

## **TECHNICAL SPECIFICATIONS**

### **ED-WIND DIRECTION SENSOR COS/SIN 4KHz**

<b>Measuring Range</b>	0 - 360°
at wind speed	0,3 - >60 m/s
<b>Threshold Speed</b>	0.3 m/s
<b>Resolution</b>	<0.1°
<b>Damping Ratio</b>	0.4
<b>Distance Constant</b>	1 m
 <b>Resolver</b>	
Effective Electrical Angle	Brushless, built-in type 360°
Input Voltage	3 VRMS
Frequency	4 KHz
Input Current	16 mA
Electrical Error	max +/- 10 minutes
<b>Output Signal</b>	Cos and Sin to the angle with one cycle output voltage in one revolution.
<b>Operating Temperature</b>	-40 to +70°C
<b>Electrical Connections</b>	5-pole LEMO plug Terminal 1: Cos High Terminal 2: Cos/Sin Low Terminal 3: Sin High Terminal 4: Carrier High Terminal 5: Carrier Low
<b>Materials</b>	Body of brass, primed and painted. Vane of anodized aluminium. Ball bearings, shaft and counterbalance of stainless steel.
 <b>Mechanical Specifications</b>	
Height	355mm
Rotating Diameter of Vane	350mm
Weight	1.4 Kg
Mounting Hole	Ø 25mm
<b>180° Point (South)</b>	The 10mm mounting bolt and cable socket are aligned to 180°, i.e. pointing towards South. <b>REMARK:</b> Old versions (and the Vestas Model) have the bolt and socket aligned to 0°, i.e. pointing towards North.
<b>Accessories included</b>	5-pole LEMO plug
<b>Options</b>	1: Vestas model with bolt towards North 2: Bottom mounted plug
<b>EU Declaration of Conformity</b>	EN61000-6-3 Emission EN61000-6-2 Immunity
<b>Warranty</b>	One Year against faulty materials or workmanship.
<b>Maintenance</b>	
Annually	Check of cable, plug, ball bearings, vane and body.
Every Second Year	Annually check and change of ball bearings.

**Serial no.:**\_\_\_\_\_

**Options:**\_\_\_\_\_

**Date:**\_\_\_\_\_

**Sign:**\_\_\_\_\_